


SECTION A-A



SECTION B-B

1. USE NUMBER AND SIZE OF SUPPORTS AS SHOWN ON THE SUPPORT CHART IN PROJECT PLANS.
2. FABRICATE SIGN PANEL SECTIONS WITH SHEETS 4'-0" WIDE. WHEN FABRICATING SIGNS WHICH ARE NOT MULTIPLES OF 4'-0" IN WIDTH, DO NOT CUT MORE THAN TWO SHEETS TO LESS THAN 4'-0" IN WIDTH. USE PANELS NOT LESS THAN 1'-0" IN WIDTH.
3. SEE NCDOT STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES FOR TYPE OF MATERIAL TO BE USED FOR SIGN PANELS, HANGER ASSEMBLIES, AND SUPPORTS.
4. USE GALVANIZED STEEL BACKING PLATES AND MOUNTING BOLTS.
5. SEE STANDARD DETAILS FOR TYPE "B" SIGNS WHEN TYPE "B" SECONDARY SIGN MOUNTING IS REQUIRED.
6. USE THE SAME DETAILS FOR TYPE "A" SECONDARY SIGNS AS FOR TYPE "A" SIGNS.
7. THE VERTICAL DIMENSION BETWEEN PRIMARY AND SECONDARY SIGNS IS TWO (2) INCHES.
8. ADJUST STIFFENERS TO AVOID CONFLICT WITH SUPPORTS.
9. FABRICATE EACH SIGN WITH AN APPROVED VHB ACRYLIC TAPE WITH FULL FACE CONTACT BETWEEN "Z" BARS AND SIGN PANELS AND BETWEEN SPLICE PLATES AND SIGN PANELS.
10. SEE ROADWAY STANDARD 901.70 FOR SUPPORT AND "Z" BAR SPACING.
11. FABRICATE SIGNS TALLER THAN 12'-0" AS TWO SEPARATE SIGNS WITH A HORIZONTAL SPLICE. LOCATE STRINGERS ON EACH SECTION OF THE SIGN BY THE SIGN STRINGER CHART (SEE ROADWAY STANDARD 901.70).
12. FABRICATE SIGNS TALLER THAN 12'-0" BUT SHORTER THAN 14'-6" WITH A HORIZONTAL SPLICE LOCATED 7'-0" FROM BOTTOM OF SIGN.
13. FABRICATE SIGNS TALLER THAN 14'-6" WITH A HORIZONTAL SPLICE LOCATED AT LEAST HALF THE SIGN HEIGHT FROM THE BOTTOM WITH THE TOP HALF AT LEAST 7'-0" HIGH.
14. SEE ROADWAY STANDARD 901.80 FOR DETAILS SHOWING SIGN MOUNTING TO SUPPORTS.